

The JP Gasoline Series features a powder coated steel frame and base plate with 1¼-inch tube handles and flat-free tires. Designed for excellent balance and mobility, this powerful direct drive series is highly recommended for contractor jobs.

JP Series

Pump:

- Forged brass manifold
- Thermal relief valve
- In-line water strainer

Unit Includes:

- Quick connect nozzles - 0°, 15° and 25°
- 50-foot x ¾-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off

Limited Warranties:

- 1 year Mi-T-M unloader
- 3 year Honda engine
- 7 year pump

Certifications:

- Intertek - Certified to UL-1776



JP-2703-3MHB

Cold Water – Gasoline – Direct Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JP-2403-3MHB	2400	2.4	196cc Honda GX200 OHV	Mi-T-M	3-0415	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2703-3MHB	2700	2.4	196cc Honda GX200 OHV	Mi-T-M	3-0415	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-3003-3MHB	3000	3.0	270cc Honda GX270 OHV	AR	3-0389	Mi-T-M, adjustable pressure	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3504-3MHB	3500	3.5	389cc Honda GX390 OHV	AR	3-0310	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MHB	4000	3.5	389cc Honda GX390 OHV	AR	3-0310	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0005	48-in. insulated dual lance	All models
851-0338	50-ft. x ¾-in. non-marking hose	All models	CX-0083	External bypass system	JP-2403-3MHB & JP-2703-3MHB
AW-8400-0021	Low pressure detergent injector	All models	CX-0084	External bypass system	JP-3504-3MHB & JP-4004-3MHB