

The Job Site Series of kerosene indirect heaters provide 100% clean, dry heat for buildings and construction sites where the heat will be ducted into a building.

MH-0125-OMIH shown with air ducting, 68-4007 and duct adapter, 68-4004

# Kerosene Indirect Ductable

**Frame:**

- Powder coated steel frame, handle and tank

**Burner:**

- Direct spark ignition

**Components:**

- Suitable for air ducting
- Electronic flame control
- Automatic ignition
- Automatic fuel shut-off

**Limited Warranty:**

- 1 year

**Certifications:**

- CSA Certified - US and Canada

**Factory Tested for Multiple Fuels:**

- Kerosene
- No. 1 and No. 2 fuel oil

**Important Notes:**

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Must be plugged into an approved standard electrical outlet for operation



## Job Site Series – 92,000 & 125,000 BTU

MODEL NO.	MH-0092-OMIH	MH-0125-OMIH
HEAT OUTPUT	92,000 BTU	125,000 BTU
HOT-AIR FLOW	557 CFM	1,180 CFM
AC POWER	115V, 60Hz, 1Ø, 4.0 Amps	115V, 60Hz, 1Ø, 7.0 Amps
POWER CONSUMPTION	250 watts	460 watts
FAN STATIC PRESSURE	0.5in. WC	0.7in. WC
FUEL TANK CAPACITY	12.0 gallons	14.0 gallons
FUEL CONSUMPTION	0.66 gal./hr.	0.9 gal./hr.
FUEL PUMP	No	Yes, high pressure
FUEL FILTER	No	Yes, heated for reliable starts
TEMPERATURE RISE	120°F	130°F
MAX. OUTPUT TEMPERATURE	240°F	240°F
MAX. OPERATING HOURS	18.0 hours	15.5 hours
MAX. DUCT SIZE (LxDIAMETER)	15ft.x12in.	25ft.x12in.
DIMENSIONS (LxWxH)	36.6x22.1x24.6in.	47x24x31in.
SHIP WT.	93 lb.	162 lb.
NET WT.	88 lb.	154 lb.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

**Accessories:**

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
68-4001	Thermostat control with 20-ft. cord - for light party use	All models	68-4006	15-ft. x 12-in. black flexible air ducting - maximum size	MH-0092-OMIH
68-4002	Thermostat control with 20-ft. cord - for construction site	All models	68-4007	25-ft. x 12-in. black flexible air ducting - maximum size	MH-0125-OMIH
68-4003	Duct adapter - required to attach ducting to the heater	MH-0092-OMIH	68-4056	Flue extension	All models
68-4004	Duct adapter - required to attach ducting to the heater	MH-0125-OMIH	68-4067	Rain cap	All models