



# WC Series



Mi-T-M Water Treatment Systems provide a better tomorrow by protecting our environment today.

Blast away heavy mud and grime from all of your industrial equipment and vehicles with one of the efficient WC Series water cannon systems. They are designed for high-volume washing and are ideal for wash bay set-ups.

# WC Series

## High-Volume Water Cannon Systems

### Typical Applications Include:

- Rental Yards
- Lumber Yards
- Mining Operations
- Heavy Equipment Dealers
- Solid Waste Haulers

### Standard with Unit:

- Single remote



The High-Volume Water Cannon System acts like a water blaster, pre-washing heavy equipment and tracked vehicles. The tough, high gallon-per-minute centrifugal system blasts away mud and dirt allowing for an easier and less timely workload during the pressure wash cycle.



WC-100-OME3

MODEL NUMBER	DESCRIPTION	GPM @ PSI	HORSEPOWER	DIMENSIONS (LxWxH)	SHIP WT.
WC-100-OME3	Mud blasting pump system with centrifugal separator (Specify 208-230V, 3Ø, 20-22.0A or 460V, 3Ø, 10.0A)	100 @ 60	7.5	42x20x66in.	500 lb.
WC-150-OME3	Mud blasting pump system with centrifugal separator (Specify 208-230V, 3Ø, 38.0A or 460V, 3Ø, 19.0A)	150 @ 80	15.0	45x21x67in.	650 lb.
WC-300-OME3	Mud blasting pump system with centrifugal separator (Specify 208-230V, 3Ø, 98.0A or 460V, 3Ø, 49.0A)	300 @ 90	40.0	58x28x75in.	1110 lb.
WC-400T-OME3	Truck wheel wash pump system, for minimum vertical lift feed, 5 or 6-ft. or tank feed (Specify 230V, 3Ø, 116.0A, 60Hz motor or 460V, 3Ø, 58.0A)	400 @ 125	50.0	58x28x75in.	1178 lb.

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
12-0084	Surge suppressor - Eliminates water logging and failures	WC-100 & WC-150
15-2001	Hose for water cannon - 100-ft. x 1½-in. ID with couplings	WC-100 & WC-150
18-2003	Adjustable spray nozzle - For #18-2006 gun turret	18-2006 turret
18-2004	High-impact nozzle with smooth bore - Needs #18-2005 shut-off valve	WC-300-OME3
18-2005	Shut-off valve for turret - Used with #18-2004 nozzle	WC-300-OME3
18-2006	Gun turret - 3-in. flange inlet, 2½" NST outlet	WC-300-OME3
18-2009	Adjustable fire hose nozzle - Adjustable spray settings, 150 GPM	WC-100 & WC-150
22-0322	Metal foot-valve - 2-in.	WC-100-OME3
22-0323	Metal foot-valve - 3-in.	WC-150-OME3
22-0324	Metal foot-valve - 6-in.	WC-300-OME3
22-0400	Metal foot-valve - 4-in.	All models
50-2001	Hose reel for 1½-in. booster hose - 100-ft.	WC-100 & WC-150
RC-0015-0001	Remote switch assembly - Comes standard with one remote	WC-100, WC-150 & WC-300

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
WX-0002	460V, 3Ø, 10.0A - Upgrades 208-230V model to operate at 460V	WC-100-OME3
WX-0003	460V, 3Ø, 19.0A - Upgrades 208-230V model to operate at 460V	WC-150-OME3
WX-0004	460V, 3Ø, 49.0A - Upgrades 208-230V model to operate at 460V	WC-300-OME3
WX-0019	Flange adapter kit	WC-300-OME3

Receive more power with less pressure. This cold water, high-volume pressure washer is the perfect answer for applications that require cleaning of heavy solids, especially from large industrial equipment. Ideal for wash bay set-ups.

## CHV Series Cold Water Electric Belt Drive Pressure Washers



CHV-0525-0ME3

### Pump:

- Belt drive diaphragm pump with pulsation dampener

### Motor:

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 10-foot power cord

### Components:

- Pressure regulator with manual dump lever and gauge
- Makeup water shut-off solenoid and flow switch on outlet
- Time delay shutdown

### Unit Includes:

- Stainless-steel long range nozzle
- 50-foot x 3/4-inch non-marking high pressure hose with quick connects
- High volume gun with adjustable pattern from straight stream to cone mist



MODEL NUMBER	DESCRIPTION	GPM @ PSI	HORSEPOWER/MOTOR	DIMENSIONS (LxWxH)	SHIP WT.
CHV-0525-0ME1	Cold water stationary electric belt driven pressure washer	25 @ 500	10.0 HP, 230V, 1Ø, 41.5A	38x23.5x24in.	432 lb.
CHV-0525-0ME3	Cold water stationary electric belt driven pressure washer	25 @ 500	10.0 HP, 230V, 3Ø, 25.6A	38x23.5x24in.	407 lb.

### Accessories:


PART NUMBER	DESCRIPTION	FITS MODELS
16-0440	Replacement gun - Replacement high-volume long range gun with adjustable pattern from straight stream to cone mist	All models
50-0185	Accessory hose reel - Add a hose reel for convenient storage of your hose; holds up to 200-ft. of 3/4-in. hose	All models

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0072	300-gallon tank - 300-gallon tank with stand, suction hose and float	All models
CX-0073	460V, 3-phase models - For when you have 460V of power available	All models
CX-0074	18-in. stand - Raises unit off of ground	All models
CX-0075	Remote start control box - For when unit is not near spraying location	All models


### Typical Water Treatment Installation

CHV-0525-0ME3 is connected to optional 300-gallon tank, CX-0072, which is connected to optional sump pump and in-ground fiberglass pit from our water treatment line.



# CHV Series Applications

Ideal for heavy mud applications.  
The higher volume GPM cuts cleaning time significantly.



**Performance Under Pressure.®**

Mi-T-M Corporation  
50 Mi-T-M Drive  
Peosta, IA 52068  
800-553-9053  
563-556-1235 fax  
corp@mitm.com  
www.mitm.com

*Distributed by:*